

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ КОТЛОВ СЕРИИ ДЕ.

Тип котла номер компоновки	Паро-произв т/ч (МВт).	Раб. дав-е, МПа (кгс/ см2)	Темп. пара,`С.	КПД, %	Расх.топлива газ, м3/ч	Габариты (LxВxH), мм.	Масса, кг
ДЕ-4-14ГМ-О 00.8022.216	4,0 (2,91).	1,4 (14)	194.	92	272	4200х 4050х 5050.	12510
ДЕ-4-14-225ГМ-О 00.8022.217	4,0 (2,91).	1,4 (14)	225.	92	282	4200х 4050х 5050.	12700
ДЕ-6,5-14ГМ-О 00.8022.316	6,5 (4,73).	1,4 (14)	194.	92	443	4800х 4050х 5050.	13910
ДЕ-6,5-14-225ГМ-О 00.8022.317	6,5 (4,73).	1,4 (14)	225.	92	457	4800х 4050х 5050.	14130
ДЕ-6,5-24ГМ-О 00.8022.317- 01	6,5 (4,73).	2,4 (24)	220.	92,5	457	4800х 4050х 5050.	16630
ДЕ-10-14ГМ-О 00.8022.428	10 (7,27).	1,4 (14)	194.	93,5	671	6530х 4050х 5050.	17680

ДЕ-10-14-225ГМ-О 00.8022.427	10 (7,27).	1,4 (14)	225.	93,5	695	6530x 4050x 5050.	18580
ДЕ-10-24ГМ-О 00.8022.428-01	10 (7,27).	2,4 (24)	220.	93,5	671	6575x 4050x 5050.	20260
ДЕ-10-24-250ГМ-О 00.8022.428-01	10 (7,27).	2,4 (24)	250.	93,5	695	6575x 4050x 5050.	21290
ДЕ-16-14ГМ-О 00.8022.520	16 (11,68).	1,4 (14)	194.	93,5	1088	8555x 5240x 6072.	20750
ДЕ-16-24ГМ-О 00.8022.520-01	16 (11,68).	2,4 (24)	220.	93,5	1088	8555x 5240x 6072.	23660
ДЕ-16-14-225ГМ-О 00.8022.521	16 (11,68).	1,4 (14)	225.	93,5	1124	8555x 5240x 6072.	22110
ДЕ-16-24-250ГМ-О 00.8022.521-01	16 (11,68).	2,4 (24)	250.	93,5	1124	8555x 5240x 6072.	23250

ДЕ-16-24-380ГМ-О 00.8022.522	16 (11,68).	2,4 (24)	380.	93,5	1296	8555x 5240x 6072.	25690
ДЕ-25-14ГМ-О 00.8022.658	25 (18,25).	1,4 (14)	194.	93,5	1670	10095x 5240x 6072.	27850
ДЕ-25-14-250ГМ-О 00.8022.644	25 (18,25).	1,4 (14)	250.	93,5	1740	10095x 5240x 6117.	28360
ДЕ-25-15-270ГМ-О 00.8022.662	25 (18,25).	1,5 (15)	270.	93,5	1803	10095x 5240x 6117.	29200
ДЕ-25-15-285ГМ-О 00.8022.649	25 (18,25).	1,5 (15)	285.	93,5	1879	10095x 5240x 6117.	32030
ДЕ-25-15-300ГМ-О 00.8022.662-01	25 (18,25).	1,5 (15)	300.	93,5	1880	10095x 5240x 6117.	31245
ДЕ-25-24ГМ-О 00.8022.658- 01	25 (18,25).	2,4 (24)	220.	93,5	1670	10095x 5240x 6117.	30840

ДЕ-25-24-250ГМ-О 00.8022.644-01	25 (18,25).	2,4 (24)	250.	93,5	1762	10095x 5240x 6117.	31430
ДЕ-25-24-380ГМ-О 00.8022.654	25 (18,25).	2,4 (24)	380.	93,5	2008	10095x 5240x 6117.	32760