

**ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ КОТЛОВ ДКВР РАБОТАЮЩИХ НА УГЛЕ И АНТРАЦИТЕ.**

Тип котла номер компоновки	Паро-произв т/ч (МВт).	Раб. дав-е, МПа (кгс/ см2)	Темп. пара, °С.	КПД, %	Расх.топлива, кг/ч	Габариты (LxВxН), мм.	Масса, кг
ДКВр-2,5-13С (ПТЛ-РПК) 00.8002.103	2,5 (1,818).	1,3 (13)	194.	82	284	5913x 4300x 5120.	6886
ДКВр-4-13С (ПТЛ-РПК) 00.8002.200	4,0 (2,91).	1,3 (13)	194.	82	450	7203x 4590x 5018.	8170
ДКВр-4-13-250С (ПТЛ-РПК) 00.8002.201	4,0 (2,91).	1,3 (13)	250.	82	474	7203x 4590x 5018.	9497
ДКВр-6,5-13С (ПТЛ-РПК) 00.8002.300	6,5 (4,73).	1,3 (13)	194.	82	726	8210x 4695x 5170.	11934
ДКВр-6,5-23С (ПТЛ-РПК) 00.8002.300-02	6,5 (4,73).	2,3 (23)	220.	82	726	8210x 4695x 5170.	13893
ДКВр-6,5-13-250С (ПТЛ-РПК) 00.8002.301	6,5 (4,73).	1,3 (13)	250.	82	767	8526x 4695x 5170.	12215

ДКВр-6,5-23-370С (ПТЛ-РПК) 00.8002.301-02	6,5 (4,73).	2,3 (23)	370.	82	767	8526x 4695x 5170.	14513
ДКВр-6,5-13С (ТЛЗ) 00.8002.306	6,5 (4,73).	1,3 (13)	194.	82	726	8526x 4695x 5530.	12025
ДКВр-6,5-23С (ТЛЗ) 00.8002.306-01	6,5 (4,73).	2,3 (23)	220.	82	726	8526x 4695x 5530.	14056
ДКВр-6,5-13-250С (ТЛЗ) 00.8002.307	6,5 (4,73).	1,3 (13)	250.	82	767	8520x 5273x 5530.	12215
ДКВр-6,5-23-370С (ТЛЗ) 00.8002.307-02	6,5 (4,73).	2,3 (23)	370.	82	767	8520x 5273x 5530.	14513
ДКВр-10-23С 00.8002.400-01	10 (7,27).	2,3 (23)	220.	84	1100	8450x 5830x 7100.	18089
ДКВр-10-13С 00.8002.406	10 (7,27).	1,3 (13)	194.	84	1100	8760x 5830x 7260.	16349

ДКВр-10-23С 00.8002.406-01	10 (7,27).	2,3 (23)	220.	84	1100	8760х 5830х 7260.	18442
ДКВр-10-13С, антрацит, 00.8002.408	10 (7,27).	1,3 (13)	194.	87	1100	9200х 5830х 7000.	17484
ДКВр-10-23С, антрацит, 00.8002.408-01	10 (7,27).	2,3 (23)	220.	87	1100	9200х 5830х 7000.	19472
ДКВр-10-13-225С, антрацит, 00.8002.409	10 (7,27).	1,3 (13)	225.	87	1100	9300х 5830х 7100.	17658
ДКВр-10-23-370С, антрацит, 00.8002.409-01	10 (7,27).	2,3 (23)	370.	84	1100	9300х 5830х 7100.	20331
ДКВр-10-13-250С 00.8002.401	10 (7,27).	1,3 (13)	250.	84	1180	8450х 5830х 7100.	16349
ДКВр-10-23-370С 00.8002.401-01	10 (7,27).	2,3 (23)	370.	84	1180	8450х 5830х 7100.	18918

ДКВр-10-13-250С 00.8002.407	10 (7,27).	1,3 (13)	250.	84	1180	8760x 5830x 7260.	16531
ДКВр-10-23-370С 00.8002.407-01	10 (7,27).	2,3 (23)	370.	84	1180	8760x 5830x 7210.	19302
ДКВр-20-13С 00.8002.609	20 (14,54).	1,3 (13)	194.	86	2230	11500x 5970x 7660.	43419
ДКВр-20-23С 00.8002.609-01	20 (14,54).	2,3 (23)	220.	86	2230	11500x 5970x 7660.	46183
ДКВр-20-13-250С 00.8002.603	20 (14,54).	1,3 (13)	250.	86	2230	11500x 5970x 7660.	43840
ДКВр-20-23-250С 00.8002.603-01	20 (14,54).	2,3 (23)	250.	86	2230	11500x 5970x 7660.	46632
ДКВр-20-23-370С 00.8002.605	20 (14,54).	2,3 (23)	370.	86	2230	11500x 5970x 7660.	47937

ДКВр-20-13С, антрацит, 00.8002.607	20 (14,54).	1,3 (13)	194.	84	4600	11500х 5970х 7660.	42025
ДКВр-20-23С, антрацит, 00.8002.607-01	20 (14,54).	2,3 (23)	220.	84	4600	11500х 5970х 7660.	44825